RACK HIGH VOLTAGE

51.2V 200Ah

LITHIUM Battery



PRODUCT FEATURE

- FLEXIBLE EXPANSION
- BATTERY PROTECTION
- LONG-TERM RELIABILITY
- ECONOMIC
- WIDE COMPATBILITY
- IP20

Email:info@sailsolarpv.com **Web**: www.sailsolarpv.com/www.sailsolaress.com
Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China

SAIL SOLAR

RACK HIGH VOLTAGE LITHIUM BATTERY

DATASHEET

MODEL	
Battery Type	LiFePO4
Nominal Battery Energy	10.24kWh
Nominal Capacity	200Ah
Nominal Voltage	51.2V
Net Weight	80kg
Dimension(W/D/H)	442/620/223mm
Communication	RS232/RS485/CAN/BLUETOOTH/WIFI
Cycle Life*	8000 cycles 90% DOD,0.5C
Protection Level	IP20
Expansion	Up to 15 units in series
Compatible Inverters	Deye/GoodWe/Solis/SAJ/Sinexcel/Hoymiles/Growatt/Ecatus/Sermatec/ATESS/Sunways etc.
Certification & Safety Standard	UN38.3, MSDS, IEC62619, CE, UL1973, UL2054

Rack Type	SAS-112.64KWH-R	SAS-122.88KWH-R	SAS-133.12KWH-R	SAS-143.36KWH-R	SAS-153.6KWH-R
Battery Module Quantity	11units	12units	13units	14units	15units
Nominal Battery Energy	112.64kWh	122.88kWh	133.12kWh	143.36kWh	153.6kWh
Nominal Capacity	200Ah	200Ah	200Ah	200Ah	200Ah
Nominal Voltage	563.2V	614.4V	665.6V	716.8V	768V
Max.Power Output	112.64kW	122.88kW	133.12kW	143.36kW	153.6kW
Discharge Cut-off Voltage	484V	528V	572V	616V	660V
Charge Cut-off Voltage	624.8V	681.6V	738.4V	795.2V	852V
Recommend Charging Current	100A	100A	100A	100A	100A
Recommend Discharging Current	100A	100A	100A	100A	100A
Max Charge/Disharge Working Current（A）	200A	200A	200A	200A	200A
Net Weight	1078KG	1176KG	1274KG	1372KG	1470KG
Working temperature	Charge : 0 ~ 55℃ / Discharge : -20℃ ~ 55℃				
Design Life	15 years+				

*File version: 2026V1-EN
*Weight and Size of the battery module is based on the actual product,
*Specifications may vary during continuous improvements, pls contactus for latest details.
*The installation of battery packs is related to product quality assurance, safe and stable operation. Please follow the requirements of the user manual for standardized installation, use, and routine maintenance
*Each column can hold a maximum of 8 batteries plus one high-voltage box, please confirm the number of batteries per column with the sales team

Email:info@sailsolarpv.com **Web**: www.sailsolarpv.com/www.sailsolaress.com
Add: Cross Border E-Commerce Supervision Zone, Yulei Road, Hefei, Anhui, China

SAIL SOLAR